

# ULTRA PEARL

HIGH SOLID - STYRENE FREE - LOW VOC'S  
WET LOOK - SLIP RESISTANT - FANTASTIC DURABILITY

**Efficient:**

Fast drying (15-20 minutes)  
Reduces floor stripping cycles  
Burnishable  
Dries with high gloss  
Reduces alkalinity  
Easy to clean and maintain  
Contains alkaline scavengers

**Environmentally Preferable:**

Certified by EcoLogo®  
Styrene Free  
Zinc Free

**Economic:**

Covers 2400-3000 sf/gallon



# PEARL

## DESCRIPTION

Ultra Pearl utilizes 'Bottom Up Drying Technology' to allow walk on easy repairs, while the floor finish is still wet. Because of Ultra Pearl's supreme adhesion abilities, it can be used on all types of hard floor surfaces including Natural Stone, Terrazzo, Ceramic Tile, Wood, Concrete, Rubber, VAT and VCT.

- Economical
- Highly Durable and Burnishable
- Resistant to black heel marks
- Can walk on for easy repairs
- Can be used on all types of resilient hard floors.
- Resistant to pad burns and soil embedment.

'Ultra Pearl' also possesses a zinc free environmentally safer polymer. Low level maintenance requires the use of 'Cleaner and Conditioner' equipped with 'Electrolytic Cleaning Technology' that will effectively maintain and restore the vibrancy of the Ultra Pearl floor finish.

### ULTRA TECHNOLOGY USED:

1. NON-STYRENE CONSCIOUS POLYMER TECHNOLOGY
2. INTERNAL THERMAL CATALYST CURING AND DRYING AGENT



## Properties

Appearance: Milky white  
Finish Type: Aliphatic Acrylic Polymer (Super Durable)  
VOC's: 4 gm/L  
Solid Content: 24%  
pH: 8.5  
Weight/Gallon: 10 lb  
Coverage:  
2500-3000 sq. ft./gallon  
Soil Resistance: Excellent  
Drying Time: 10-15 minutes  
(depending on humidity)  
Color of Dry Film: Water Clear  
Application Temperature:  
50 degrees F (Minimum)  
Storage Temperature:  
40 degrees F - 85 degrees F  
Storage Stability:  
1 year under normal conditions  
Freeze Thaw Stability:  
Passes one to three cycles

Ultra Pearl exceeds Slip Resistance standards when tested according to ASTM D3052-87: 0.5 - 0.85 (Slip Resistant)

This product meets Ecologo's environmental standard for industrial and institutional cleaners based on its reduced human and aquatic toxicity and reduced smog production potential.

**KEEP OUT OF REACH  
OF CHILDREN DANGER**

**ULTRACHEM LABS®**

1462 E. Mission Blvd  
Pomona, CA 91766 USA

toll-free 1-(888)-858-7224

local 1-(909)-620-0949

info@ultrachemlabs.com

www.ultrachemlabs.com

